

What is claimed is:

1(currently amended). An arrangement for attaching hygienic articles such that their height will be adjustable, comprising:

a wall-mounting rod that has a continuous, guiding profile for guiding a slide, extending over ~~a its~~ full length **of the wall-mounting rod between ends,**

at least one bracket for fastening the wall-mounting rod to a surface, wherein the arrangement leaves clear that part of the guiding profile used for guiding the slide.

2(currently amended). An arrangement according to claim 1, where the bracket is attachable to the wall-mounting rod in the vicinities of ~~its~~ **the** ends.

3(currently amended). An arrangement according to claim 1, wherein the bracket is attachable to the wall-mounting rod by one of inserting ~~it into same~~ **the bracket into the wall-mounting rod,** and latching ~~it onto same~~ **the bracket onto the wall-mounting rod.**

4(currently amended). An arrangement according to claim 1, having **plural** ~~several~~, at least partially identically shaped **said** brackets.

5(previously presented). An arrangement according to claim 1, where the at least one bracket is configured for attachment to two sections of a wall-mounting rod that are to be coaxially arranged.

6(currently amended). An arrangement according to claim 1, where the at least one bracket has two attachment sections, one each at least near to each of ~~the its~~ ends, one of which is configured for attaching a terminating component for terminating the wall-mounting rod.

7(previously presented). An arrangement according to claim 6, where the attachment section for attaching the terminating component has a device for one of a form-fit and an interference-fit attachment of the terminating component.

8(previously presented). An arrangement according to claim 6, where both attachment sections have means for guiding the sections of the wall-mounting rod.

9(previously presented). An arrangement according to claim 6, where the two attachment sections are separated by a land.

10(previously presented). An arrangement according to claim 1, where the wall-mounting rod has a groove forming a guiding profile.

11(previously presented). An arrangement according to claim 10, where a lower terminating component has an extension of the groove.

12(currently amended). An arrangement according to claim 1, where the wall-mounting rod forms a length of ~~hollow, profiled~~ stock **with a hollow profile** and the bracket engages an interior of ~~the its~~ hollow profile.

13(previously presented). An arrangement according to claim 1, where accessory items are attachable to the bracket.

14(previously presented). An arrangement according to claim 6, wherein the terminating component comprises a terminating collar.

15(previously presented). An arrangement according to claim 9, wherein the land forms a joint.

16(previously presented). An arrangement according to claim 10, wherein the groove is on a front surface of the wall-mounting rod.

17(previously presented). An arrangement according to claim 13, wherein the accessory items are attachable to the bracket at a land separating two attachment sections

18(previously presented). An arrangement according to claim 17, wherein the land is broadened for attachment of the accessory items.